according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier FX PROTECT G-FINITY CNT GRAPHENE COATING

Substance / mixture mixture

UFI 1PJ1-X031-D004-VK1H

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Preparation protecting against water

Mixture uses advised against

The product should not be used in ways other than those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name FX International Sp. z o.o.

Address Strefa Gospodarcza 4, Rydułtowy,

44-280 Poland +48 577 899 066 biuro@fxprotect.pl

Competent person responsible for the safety data sheet

Name FX International Sp. z o.o. E-mail biuro@fxprotect.pl

1.4. Emergency telephone number

Phone

E-mail

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Corr. 1, H314 Skin Sens. 1, H317 STOT SE 3, H336

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Causes severe skin burns and eye damage. May cause an allergic skin reaction.

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

n-butyl acetate

 $Hydrocarbons, C10\text{-}C13, n\text{-}alkanes, isoalkanes, cyclics,} < 2\% \ aromatics$

Dimethyl hydrogen cyclosilazanes, dimethyl polymers, methyl hydrogen silazanes, products

reaction with 3-(trimethoxysilyl)-1-propanam

Metylotrimetoksysilan

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

Hazard statements

H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.
P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to by handing over to the person authorized to dispose of waste or by

returning to the supplier.

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1	n-butyl acetate	25-50	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	1
EC: 918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	25-50	Asp. Tox. 1, H304	
CAS: 475645-84-2 EC: 640-361-7	Dimethyl hydrogen cyclosilazanes, dimethyl polymers, methyl hydrogen silazanes, products reaction with 3-(trimethoxysilyl)-1-propanam	10-25	Flam. Liq. 2, H225 Acute Tox. 4, H302 Skin Corr. 1, H314 Aquatic Chronic 3, H412	
CAS: 1185-55-3 EC: 214-685-0	Metylotrimetoksysilan	10-25	Flam. Liq. 2, H225 Skin Sens. 1, H317	
Index: 612-108-00-0 CAS: 919-30-2 EC: 213-048-4	3-aminopropyltriethoxysilane	2,5-10	Acute Tox. 4, H302 Skin Corr. 1B, H314	
CAS: 2943-75-1 EC: 220-941-2	Trietoksyoktylsilan	1-2,5	Skin Irrit. 2, H315 Aquatic Chronic 2, H411	
Index: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9	toluene	<1	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Repr. 2 (***), H361d STOT RE 2 (**), H373	1, 2
Index: 050-030-00-3 CAS: 77-58-7 EC: 201-039-8	dibutyltin dilaurate	<1	Muta. 2, H341 Repr. 1B, H360FD STOT RE 1, H372 (immune system)	2
Index: 603-096-00-8 CAS: 112-34-5 EC: 203-961-6	2-(2-butoxyethoxy)ethanol	<1	Eye Irrit. 2, H319	1, 2

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-001-00-X CAS: 67-56-1 EC: 200-659-6	methanol		Flam. Liq. 2, H225 Acute Tox. 3, H301+H311+H331 STOT SE 1 (**), H370 Specific concentration limit: STOT SE 1, H370: $C \ge 10 \%$ STOT SE 2, H371: 3 % $\le C < 10 \%$	1, 2

Notes

- ** another exposure route cannot be ruled out
- *** reproductive toxicity: supplementary letters specify whether fetal harm (d) or fertility harm (f) may occur
- 1 A substance for which exposure limits are set.
- 2 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Take care of your own safety, do not let the affected person walk! Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Take off any rings, watches, bracelets before or during washing if worn in the contaminated areas of the skin. Rinse contaminated areas with a flow of water, lukewarm at best, for 10-30 minutes; do not use any brush, soap or neutralizers. Depending on the situation, call the medical rescue service and always ensure medical treatment. Rinse cautiously with water for several minutes. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. Cough, headache. May cause drowsiness or dizziness.

If on skin

Causes severe skin burns. May cause an allergic skin reaction.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value	Note
	OEL 8 hours	241 mg/m³	
n-butyl acetate (CAS: 123-86-4)	OEL 8 hours	50 ppm	
In-butyl acetate (CAS: 123-80-4)	OEL 15 minutes	723 mg/m³	
	OEL 15 minutes	150 ppm	

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

European Union

Commission Directive 2006/15/EC

Substance name (component)	Type	Value	Note
	OEL 8 hours	192 mg/m ³	
talvana (CAS, 100 00 2)	OEL 8 hours	50 ppm	Skin
toluene (CAS: 108-88-3)	OEL 15 minutes	384 mg/m ³	Skin
	OEL 15 minutes	100 ppm	
	OEL 8 hours	67,5 mg/m ³	
2 (2 hytayyathayy)athanal (CAS, 112 24 5)	OEL 8 hours	10 ppm	
2-(2-butoxyethoxy)ethanol (CAS: 112-34-5)	OEL 15 minutes	101,2 mg/m ³	
	OEL 15 minutes	15 ppm	
methanol (CAS: 67-56-1)	OEL 8 hours	260 mg/m ³	Skin
methanol (CAS: 07-30-1)	OEL 8 hours	200 ppm	SKIII

8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

liquid

data not available

Respiratory protection

Mask with a filter in a poorly ventilated environment.

Thermal hazard

Not available.

Physical state

Colour

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Odour	data not available
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	50 °C
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	19 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	data not available
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	data not available
Relative vapour density	data not available
Particle characteristics	data not available
Other information	

9.2.

not available

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes severe skin burns and eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances *

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information

14.1. UN number or ID number

UN 2924

14.2. UN proper shipping name

FLAMMABLE LIQUID, CORROSIVE, N.O.S.

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III - substances presenting low danger

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code

Safety signs

38 2924

FC



Air transport - ICAO/IATA

Packaging instructions passenger 354
Cargo packaging instructions 365

Marine transport - IMDG

EmS (emergency plan) F-E, S-C MFAG 700

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

2-(2-butoxyethoxy)ethanol

Restriction	Conditions of restriction
55	1. Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of spray paints or spray cleaners in aerosol dispensers in concentrations equal to or greater than 3 % by weight.
	2. Spray paints and spray cleaners in aerosol dispensers containing DEGBE and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27 December 2010.
	3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that paints other than spray paints containing DEGBE in concentrations equal to or greater than 3 % by weight of that are placed on the market for supply to the general public are visibly, legibly and indelibly marked by 27 December 2010 as follows:
	"Do not use in paint spraying equipment".

dibutyltin dilaurate

Restriction	Conditions of restriction
30	Without prejudice to the other parts of this Annex the following shall apply to entries 28 to 30:
	1. Shall not be placed on the market, or used, — as substances,
	— as substances, — as constituents of other substances, or,
	— in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or
	greater than:
	- either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, - the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008.
	Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows:
	"Restricted to professional users".
	2. By way of derogation, paragraph 1 shall not apply to:
	(a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC;
	(b) cosmetic products as defined by Directive 76/768/EEC;
	(c) the following fuels and oil products:
	 motor fuels which are covered by Directive 98/70/EC, mineral oil products intended for use as fuel in mobile or fixed combustion plants,
	— fuels sold in closed systems (e.g. liquid gas bottles);
	(d) artists' paints covered by Regulation (EC) No 1272/2008;
	(e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date.
	(f) devices covered by Regulation (EU) 2017/745.

methanol

Restriction	Conditions of restriction	
	Shall not be placed on the market to the general public after 9 May 2019 in windscreen washing or defrosting fluids, in a	
	concentration equal to or greater than 0,6 % by weight.	

toluene

Restriction	Conditions of restriction
48	Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by
	weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risl	phrases used in	the safety data sheet
-------------------------	-----------------	-----------------------

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H341 Suspected of causing genetic defects.

H360FD May damage fertility. May damage the unborn child.

H361d Suspected of damaging the unborn child.

H370 Causes damage to organs.
H371 May cause damage to organs.

H372 Causes damage to the immune system through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.
P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to by handing over to the person authorized to dispose of waste or by

returning to the supplier.

A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures

EC Identification code for each substance listed in EINECS

EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan EU European Union

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals

 ICAO
 International Civil Aviation Organization

 IMDG
 International Maritime Dangerous Goods

 IMO
 International Maritime Organization

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization

9/10

according to Commission Regulation (EU) 2020/878 as amended

FX PROTECT G-FINITY CNT GRAPHENE COATING

Creation date 29th April 2023

Revision date Version 2.0

IUPAC International Union of Pure and Applied Chemistry

log Kow Octanol-water partition coefficient
OEL Occupational Exposure Limits
PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

UN Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB Substances of unknown or variable composition, complex reaction products or biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Acute Tox. Acute toxicity

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Asp. Tox. Aspiration hazard
Flam. Liq. Flammable liquid
Muta. Germ cell mutagenicity
Repr. Reproductive toxicity
Skin Corr. Skin corrosion
Skin Sens. Skin sensitization

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.